



**SAFETY SYSTEM®**  
YOUR PROTECTOR

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciaci, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575  
Fax +39 02.90394441

**TECHNICAL SHEET**

export@sirsafety.com  
www.sirsafety.com




<b>Name: ULTRA earplugs 200 pairs</b>	<b>Code: FC117</b>	<b>FC11 EAR PROTECTION - EAR PLUGS</b>
---------------------------------------	--------------------	--

**Description**  
Soft disposable earplugs in polyurethane foam, 27 mm long. Latex free.  
Pack of 200 pairs in single poly bags.

SNR 37 dB  
Hertz frequency: H Attenuation = 36  
Hertz frequency: M Attenuation = 34  
Hertz frequency: L Attenuation = 33  
Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:125/38.1/4.9/33.2;  
Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:250/37.9/6.3/31.6;  
Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:500/39.6/6.5/33.1;  
Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:1000/37.7/4.2/33.5;  
Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:2000/37.3/3.5/33.8;  
Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:4000/48.4/5.1/43.3;  
Freq.(Hz)/Attenuation Med./Dev. standard/Value APV:8000/45.9/4.5/41.4;

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.



Category <b>III</b>	Colours	Available Sizes In stock: U
Quantity/Carton  <b>10</b>	EC Standards EN 352-2	Important Information Suitable in noisy and extremely noisy environments.  Make sure the device is in good condition before use. Once you become aware of a damage, you should immediately replace it.  Keep in a cool dry place, far from heat sources. Keep the earplugs clean, so they do not attract dust and dirt before use, promoting proper hygiene in the ear canal.  Disposable device: replace the earplugs after use.
Dexterity		Storage and cleaning