

Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 - Fax +39 075.8048686

Name: STRATOS 3 safety harness

Code: FD1118

VAT Nr. IT 03359340548

20090 Cusago Milano

Tel. +39 02.90394575

Fax +39 02.90394441

Viale Europa 74

TECHNICAL SHEET

export@sirsafety.com www.sirsafety.com





118 FD11 FALL ARREST DEVICES - HARNESSES

Description

Fall arrest and work positioning harness with sternal attachment. In polyester, 44 mm wide, with 23 kN breaking force. It features: ATTACHMENTS: 1 dorsal Dofattachment and 1 front/chest Dofa attachment; 1 ventral Dofattachment, waist height, on front for rope access, and 2 lateral Dofatings for work positioning. ADAPTABILITY: fully adjustable shoulder straps, legs loops and waist belt.

ADVANTAGES: padded shoulder straps, waistbelt and leg loops. The shoulder straps and leg loops are fitted with automatic quick-attach buckles. 2 tool rings and one larger extra ring on the back for carabiners and accessories. Hooks inserted on shoulder straps to setsingle lanyards. ERGONOMICS: stretching straps for prolonged comfort. Specially padded straps for better shock absorption and greater user comfort. WEIGHT: 2.40 kg

MAXIMUM LOAD: 140 kg

Technical Specifications:

- Elastic Loops: specially designed to retain the excess strap while adjusting.

- Automatic Buckles: in stainless steel.

- Lanyard Keepers: on both sides for attaching lanyards safely.

- Ventral D-Ring: for rope access, rescue and other applications, making the harness multi-purpose.

- Shoulders straps and leg loops: fully padded, with quick attach buckles.
- The particular padding ensures better shock absorption and air

circulations.

 \mathbf{E}_{AD} ate: back plate enclosing the two crossing dorsal straps, keeping the D-ring in place, even after a fall.

- Front attachment: upper sternal D-ring ergonomically placed, to be used as frontal anchor point for fall protection.

Work positioning belt: padded, with lateral D-rings for extra comfort while working. Features a back handle for attaching extra accessories.
Combination Sliders: easy to adjust, even with one hand.

Advantages:

- Shoulders, waist and leg straps fully padded.

- Shoulder and leg straps are equipped automatic with quick-release buckles.

- 2 tool loops and an extra large loop on the back for carabiners and accessories.

- Loops on shoulder straps for positioning individual ropes.

- Stretching straps for prolonged comfort.

- Specially designed seat belt for prolonged comfort.

- Padded harness straps for better shock absorption and increased user comfort.

Metallic components: galvanised steel.

Stitching thread: High tenacity polyamide.

Static Force: 15 kN o 1.530 Kg per 3 minutes per every attaching element.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.







Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 Fax +39 02.90394441 export@sirsafety.com www.sirsafety.com





Quantity/Carton	EC Standards	Important Information
	EN 358	Suitable for work at height.
1	EN 361	Read carefully the user sheet included. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.
	EN 813	Keep in a dry place, far from heat sources.
Dexterity		Storage and cleaning