

Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 Fax +39 02.90394441

TECHNICAL SHEET

FD18 FALL ARREST DEVICES - MOBILE

export@sirsafety.com www.sirsafety.com

ANCHORING DEVICES





Name: Mobile anchoring device kit

Code: FD1811


Description

Designed for easy installation and removal, the system is tensioned using the tensioner and can be fitted to any suitable anchorage point (from 2000 daN). The lifeline is designed for use by one person at a time. Maximum deflection in the event of a fall: 2.44 m. The complete kit includes:

- a comfortable and resistant bag with closure device;
- 30 mm polyester webbing carefully rolled up(maximum length 20 m);
- a spool cable tensioner;
- two fixed point anchor belts (1 m) with rings;
- two positioning lanyards item no. FD1575;
- two FD1137 fall arrest harnesses.

Using the anchor on two fixed points to a maximum distanceof 20 m, the deviceallows the normal working operations, connecting the worker equipped with a safety harness, who freely slide along the webbing through a lanyard with carabiner.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.



Category	Colours	Available Sizes
III		In stock: U
Quantity/Carton	EC Standards	Important Information
	EN 354	Assemblind and disassembling scaffoldings, covering exteriors of buildings or in other places where railing is temporally missing.
	EN 361	Read carefully the user sheet included. Make sure the item is in good condition, undamaged before use. Once you become aware
	EN 795	of a damage, you should immediately replace it.
		Keep in a cool dry place, far from heat sources.
Dexterity		Storage and cleaning