



**SAFETY SYSTEM®**  
YOUR PROTECTOR

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575  
Fax +39 02.90394441

**TECHNICAL SHEET**

**export@sirsafety.com**  
**www.sirsafety.com**



UNI EN ISO 9001:2015  
UNI EN ISO 14001:2015  
UNI EN ISO 45001:2018

<b>Name: Webbing and anchorage slings</b>	<b>Code: FD1812</b>	<b>FD18 FALL ARREST DEVICES - MOBILE ANCHORING DEVICES</b>
---	---------------------	--

**Description**

Horizontal anchorage device with polyester webbing, 35 mm wide. Adjustable length from 5 to 20 metres. Equipped with two webbing anchorage slings with rings for the anchorage points. Designed for easy installation and removal, the system is tensioned using the tensioner and can be attached to any suitable anchor point (from 2000 daN). The lifeline is designed for use by one person at a time. Maximum deflection in the event of a fall: 2.44 m.

The complete kit includes:

- a comfortable and resistant bag with closure device;
- a carefully rolled up 30 mm polyester strap (maximum length 20 m);
- a spool cable tensioner;
- two anchor belts to the fixed point (1 m) with rings.



The product has been designed and manufactured to comply with Regulation(EU) 2016/425 and subsequent amendments.

Category <b>III</b>	Colours	Available Sizes In stock: U
Quantity/Carton <b>1</b>	EC Standards EN 795	Important Information Assemblind and disassembling scaffoldings, covering exteriors of buildings or in other places where railing is temporally missing.  Read carefully the user sheet included. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.  Keep in a cool dry place, far from heat sources.
Dexterity		Storage and cleaning