

TECHNICAL SHEET

Name: VIVA LOW SHOE

Code: MB1519ZE

MB15 FOOTWEAR NEW METAL TOP SERIES

Description

Low shoe with fibreglass toecap and composite midsole, having 4 mm-constant thickness. Airmesh suede leather upper.
SOLE: (PU/PU) The special sole design assures a highly draining effect in the presence of liquids. Middle area with grooves designed to enhance grip on ladders. SRC slip resistant.
INSOLE: Insole made of multi-perforated EVA material with anti-shock properties, having variable thickness: 3 mm at the front and 10 mm in the heel area. Polyester lining. Antistatic.
LINING: In polyester, with high draining power due to the high absorbing properties of the fabric and structure.

Main features:

- Particularly wide and comfortable shape, it guarantees great comfort
- Wide-cell polyurethane gives lightness and great cushioning effect
- It adapts to all types of activities specific to industrial sectors

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.



Category

II

Colours

BLACK/RED

Available Sizes

35 - 47

Quantity/Carton

10

EC Standards

EN ISO 20345



Safety Class:S1P SRC

Important Information

Construction , Agricultural sector and Forestry, Light and heavy mechanical industry, Metallurgic industry, Handling and Logistics,Cleaners, Maintenance technicians and Installers.

The footwear should be stored in a cool dry place, far from heat sources and direct light.
Make sure footwear is in good condition, before use. If the shoes are damaged, replace them.

Clean the footwear with a soft brush and water.

Dexterity