



SAFETY SYSTEM®
YOUR PROTECTOR

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575
Fax +39 02.90394441

TECHNICAL SHEET

export@sirsafety.com
www.sirsafety.com



Name: FLAME RETARDANT bib-trousers	Code: MC5413R8	MC54 CLOTHING - FLAME RETARDANT SERIES
---	-----------------------	---

Description

Bib-trousers in 100% Flame Retardant cotton fabric, weight 315 g/m . Concealed metal zipper closure fastened with Velcro, functional side pockets with flap and Velcro, back pocket on the right side, back elastic waistband and metal side buttons, elasticated shoulder straps with metal buckles.

THE BIB-TROUSERS SHALL BE WORN IN COMBINATION WITH THE JACKET.

- It features remarkable multi-protective properties and is able to guarantee a high level of comfort while maintaining softness, lightness and breathability.
- it withstands up to 25 washes without altering the protective characteristics of the fabric.
- The full range can be produced in orange and red colours.

Suitable for protecting the operator from accidental contact with minor flames, molten metal splashes, low values of convective and radiant heat, and accidental electric contact up to 100 V of short duration.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425.

certified



Category II	Colours EMERALD GREEN	Available Sizes In stock: 44 - 62
-----------------------	---------------------------------	---

Quantity/Carton 20	EC Standards EN ISO 11611 Class:1 Values:A1	Important Information Metalworking Industry, Metallurgical Industry, Foundries, Plastic materials processing, Gas, water and electricity Industries, Firefighting Teams. Keep in a cool dry place, far from heat sources and direct light. Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it. We recommend to follow the washing instructions. Resistance up to 25 washings.
	EN ISO 11612 Limited Flame Spread:A1 Convective Heat:B1 Radiant Heat:C1 Molten Iron Splashes:E2 Contact Heat:F1	

Dexterity

Storage and cleaning