



SAFETY SYSTEM®
YOUR PROTECTOR

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciaci, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575
Fax +39 02.90394441

TECHNICAL SHEET

export@sirsafety.com
www.sirsafety.com



Name: CARBOFLAME coverall	Code: MC5637H5	MC56 CLOTHING - CARBOFLAME SERIES
----------------------------------	-----------------------	--

Description

Coverall with shirt collar, outer fabric in 87% cotton, 12% nylon and 1% carbon fibre, 255 g/m . Two-way central zipper closure with flap and Velcro, chest pockets with zipper and flaps with Velcro, loop for gas detector above right pocket; pocket on left sleeve with flap and Velcro, front slanted pockets with flap and Velcro, exterior-to-interior access on the sides, side elastic waistband. Two back pockets with flap and Velcro, knee pad pockets with Velcro closure; ruler pocket with flap and Velcro, reflective band on the shoulders, legs and arms, triple stitching.

- The entire Carboflame series is Flame Retardant and antistatic, suitable for protecting the operator from accidental contact with minor flames, molten metal splashes and accidental electric contact of short duration.
- Night safety thanks to the reflective bands.
- Version with elastic tape cuffs available upon request.

The product is designed and manufactured according to the Regulation (EU) 2016/425 and subsequent amendments.

In combination with the coverall, is it possible to wear our under garments: Carboflame undershirt art. MC5610 and Carboflame underpants art. MC5620, meeting the point A.2 of IEC 61482-2 which is stating that the electric arc protective clothing shall be used with under garments made of materials that would not melt with the arc.

VOA as Acci) aAa) B/ UOSUEVOYI Uca) aa)AEEA certified



Category III	Colours ORANGE	Available Sizes In stock: S - 3X
------------------------	--------------------------	-------------------------------------

Quantity/Carton 15	<p>EC Standards</p> <p>EN 1149-5</p> <p>EN ISO 11612</p> <p>Limited Flame Spread:A1 Convective Heat:B1 Radiant Heat:C1 Contact Heat:F1</p> <p>EN 17353</p> <p>Type:B3</p> <p>CEI EN 61482-2</p> <p>APC:1</p>	<p>Important Information</p> <p>Petrochemical Industry, Oil & Gas Industries, Mining Industry.</p> <p>Keep in a cool dry place, far from heat sources and direct light. Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it.</p> <p>We recommend to follow the washing instructions.</p>
--	--	---

Dexterity	Storage and cleaning
-----------	----------------------

