

Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 - Fax +39 075.8048686

VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 Fax +39 02.90394441

export@sirsafety.com www.sirsafety.com





Name: POLYTECH coverall Code: MC5717Q5 MC57 CLOTHING - POLYTECH SERIES

## Description

Coverall made of a technical fabric composed by 75% cotton, 24% polyester, 1% antistatic fibre fabric, weight 280 g/m. With shirt collar, military style epaulettes on the shoulders, concealed two-way zipper closure with snap buttons, two chest pockets and two front pockets all with flaps and Velcro, elastic cuffs, elastic waistband, reflective piping on the chest.

- The Polytech series ismade with a multi-purpose fabric that combines antistatic properties with resistance to flames, heat and chemical products.
- Thanks to its features it is multi-purpose, practical and resistant, breathable and comfortable.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425.

In combination with the coverall, is it possible to wear our under garments: Carboflame undershirt art. MC5610 and Carboflame underpants art. MC5620.

V@Á, anā, Án¢o^¦}an,Áanaà¦a3aÁna ÁUÒSUË/ÒÝí ÁŪcaa)åad-åÁn∈€Á certified





Petrochemical Industry, Metalworking Industry, Refining Industry, Chemical Industry, Industrial Maintenance and Assemblies, Gas, Water and Electricity Mains Maintenance and Management,

Keep in a cool dry place, far from heat sources

We recommend to follow the washing instructions.

Wash separately from other types of garments to

Make sure the garment is in good condition, undamaged and clean before use. Once you

become aware of a damage, you should

avoid the transfer of inflammable fibres.

Category

Ш

15

Colours

DARK BLUE

Available Sizes

Made to order: 38 - 38, 64 - 68

In stock: 44 - 62

Important Information

Oil & Gas industry.

immediately replace it.

and direct light.

Quantity/Carton

**EC** Standards

EN 1149-5



EN ISO 11611



Class:1 Values: A1

EN ISO 11612



Limited Flame Spread:A1 Convective Heat:B1 Radiant Heat:C1 Molten Iron Splashes:E3 Contact Heat:F1

EN 13034



Type:6

CEI EN 61482-2



ATPV (Fabric):11 ELIM (Fabric):10











Storage and cleaning