



SAFETY SYSTEM®
YOUR PROTECTOR

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575
Fax +39 02.90394441

TECHNICAL SHEET

export@sirsafety.com
www.sirsafety.com



UNI EN ISO 9001:2015
UNI EN ISO 14001:2015
UNI EN ISO 45001:2018

| | | |
|----------------------------|-----------------------|---|
| Name: Leather apron | Code: MC6511A0 | MC65 CLOTHING - LEATHER WELDING PROTECTION |
|----------------------------|-----------------------|---|

Description

Apron in 1 mm thick cowhide split leather, 60x90 cm, with FR cotton-strings closure.


- The natural features of the leather favour breathability
- The thickness of the leather assure protection and comfort
- Durability of employed material
- Also resistant to mechanical wear

Suitable for protecting the skin of the operator covered with the garments, against small drops of molten metal in activities of welding and cutting.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.



| | | |
|------------------------------|-------------------------------------|--|
| Category II | Colours LIGHT GREY | Available Sizes In stock: U |
|------------------------------|-------------------------------------|--|

| | | |
|---|--|--|
| Quantity/Carton 25 | EC Standards EN ISO 11611  Class:2 Values:A1 | Important Information Metallurgical Industry, Maintenance. Keep in a cool dry place, far from heat sources and direct light. Make sure the product is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it. The product should not be cleaned, the cleaning can be done with a brush for clothes. |
|---|--|--|

| | |
|------------------|---|
| Dexterity | Storage and cleaning  |
|------------------|---|